





Parete - Soffitto  
Wall - Ceiling





7400C



7410C



## 7400C

**7400C/1B1**

6W GX53

Fluorescente compatta / Compact fluorescent

**7400C/1U1**

60W G9

Alogena 2 PIN / 2 PIN halogen

**7400C/1Z1\***

1,5W GX53

Led bianchi alim. interno / Self-ballasted white Led

## 7410C

**7410C/1U2**

75W GU10

Alogena con riflettore / Halogen with reflector

**7410C/1U5**


50W E27 PAR20

Alogena con riflettore / Halogen with reflector




## Tipo Diffusore / Emissione

## Diffuser / Emission Tipology



VS

Vetro Satinato  
Satin Finish Glass

VT

Vetro Trasparente  
Transparent Glass

## Colori

## Colours

00

Bianco White

09

Grigio Grey

30

Antracite Anthracite

## Caratteristiche Costruttive

## Structural Construction

## STRUTTURA

- Anelli in pressofusione di alluminio Lega EN AB 46100
- Corpo in alluminio estruso Sez.Tonda Lega EN-AW 6060
- Diffusori in vetro temperato acidato / trasparente
- Dotazione : Guarnizioni in Etilene-propilene (EPDM) 40sh
- Entrata singola del cavo di alimentazione con passacavo in PVC
- Viteria esterna in acciaio Inox A2
- Verniciatura in polvere poliestere resistente alla corrosione e alle nebbie saline (ISO7523)

## CABLAGGIO

- Componentistica all'interno del corpo lampada

## CARATTERISTICHE

- Tipologia installazione : Parete / Soffitto
- Grado di protezione : IP54
- Classe di Isolamento I
- Installabile su superfici normalmente incombustibili
- Conforme alla Norma EN 60598 (CEI 34-21) e prescrizioni particolari

## STRUCTURE

- Rings die-cast aluminium - Alloy EN AB 46100
- Body extruded aluminium with round section Alloy EN-AW 6060
- Diffuser acid etched / clear toughened safety glass
- Fittings: Ethylene-propylene (EPDM) 40 sh seals
- Single cable entry with a PVC cable gland
- A2 stainless steel exterior screw fixtures
- Polyester powder paint finish resistant to corrosion and sea mist (ISO7523)

## WIRING

- Electric and wiring enclosed in lighting fixture body

## FEATURES

- Installation: Wall / Ceiling
- Degree of protection: IP54
- Insulation class I
- Can be installed on flammable surfaces
- Conforms to the standard EN 60598 (CEI 34-21) and specific provisions

## Note

## Remarks


\* Disponibile anche nei colori: **Z2** Verde  
**Z3** Rosso  
**Z4** Blu

\* Available also in these colours: **Z2** Green  
**Z3** Red  
**Z4** Blue

## Dati fotometrici


## Photometric data

## 7400C/1B1.VS



C <sub>0-180</sub> =59°				
	h (m)	d (m)	Em (lux)	E <sub>max</sub> (lux)
	1	1,1	61	86
	2	2,3	15	21
	3	3,4	7	10

## 7400C/1U1.VS



C <sub>0-180</sub> =33°+38°					
C <sub>90-270</sub> =29°+34°					
	h (m)	d1 (m)	d2 (m)	Em (lux)	E <sub>max</sub> (lux)
	1	1,5	1,3	69	95
	2	2,8	2,4	17	24
	3	4,3	3,7	8	11

Dati tecnici

Technical data

