

Application

- specially designed for ventilation of medium and large size facilities
- both for horizontal and vertical mounting

Features


- motor provided with external rotor on ball bearings and thermal protection
- body made of steel with polymeric coating
- balanced impeller
- low sound level
- completed with bracket
- IP X4



Specification

Type	Air capacity, m ³ /h	Pressure, Pa	r.p.m.	Consumption current, A	Voltage, V	Power, W	Capacitor, mFa	Sound level, dbA	Frequency, Hz	Ambient temperature, °C
200 VKM	800	500	2750	0,25	230	120	4	48	50	60
200 VKMS	1030	580	2550	0,27	230	130	4	58	50	45
250 VKM	1300	620	2600	0,70	230	155	5	60	50	50
315 VKM	1350	550	2650	0,81	230	185	6	62	50	50
315 VKMS	1750	760	2700	1,00	230	225	7	64	50	40

Dimensions, mm



Type	Ød	ØD	C	A	B	L	E	Weight, kg
200 VKM	200	344	240	25	25	350	40	6,6
200 VKMS	200	344	240	25	25	350	40	6,7
250 VKM	250	344	250	25	30	350	40	7,3
315 VKM	315	404	280	30	30	410	40	8,1
315 VKMS	315	404	280	30	30	410	40	8,1

■ Drawings

